



UPPER SECTION ERECTION INSTRUCTIONS NARROW SPAN SCAFFOLD

**LIGHT
DUTY**

25 LBS./SQ. FT. (500 LBS. MAXIMUM) 1 PERSON PER ALDEK®
PLATFORM BOARD. 500 LBS. MAXIMUM PER SCAFFOLD.

MINIMUM BRACE REQUIREMENTS FOR THIS SECTION 2 DIAGONALS, 2 HORIZONTALS

1 READ AND UNDERSTAND ALL INSTRUCTIONS ON THIS SCAFFOLD


WARNING:

FAILURE TO COMPLY WITH THESE INSTRUCTIONS MAY RESULT
IN SERIOUS INJURY.

2 SET-UP UPPER SECTION

- A** Insert stacking pins of guardrail section frames into sockets on top of vertical posts of frames of section below.

A
UPPER
SECTION
END FRAMES



- B** Position the interlock pin through aligned holes as shown (See Figure a).

Be certain that pin securely engages both the upper endframe stacking pin and the lower endframe vertical post. After the pin is engaged, the spring clip should rest flush against the vertical post as shown (See Figure b).






Figure b



- C** Attach one diagonal brace on one side of upper section and the other remaining diagonal brace to the other side to form an "X". Diagonal braces should straddle junction of upper and lower section. Attach horizontal braces on rungs of frames. To use extra horizontal braces as guardrails follow directions with handrail hangers.



- D** Move platform from base of lower section to desired height on scaffold by placing hooks on platform on rungs of frame.

NOTE: If platforms are placed on either the top rung or second rung from the top, install a guardrail or upper section to obtain proper guardrail height above platform. See instructions on these sections or consult the manufacturer.

CAUTION

READ INSTRUCTION LABEL ON UNDERSIDE OF PLATFORM

OSHA REQUIRES

TOEBOARDS, HANDRAIL AND SCREENING

CHECK OSHA & STATE CODES
FOR DETAILS OF REQUIREMENT